

In the Claims

Please amend the claims as follows:

1. (Currently Amended) A power-operated drive-in device (2) comprising a pipe arrangement (6) comprising a fall pipe (42) and a guide pipe (12), with a drive-in tool (13) for fasteners (15) and ~~with~~ a head piece (4) arranged at an outlet opening (10) of a the guide pipe (12) ~~of the drive-in device (2)~~ and having a holding device (44) that automatically receives and releases fasteners (15) sliding from the fall pipe (42) that are fed to the head piece (4) via the guide pipe (12), wherein the head piece (4) has a rotatable connection to the rest of the drive-in device (2) and is rotatable relative to the pipe arrangement (6).

2. (Original) The power-operated drive-in device of claim 1, wherein the head piece (4) has at least two fixing positions relative to the rest of the drive-in device (2).

3. (Original) The power-operated drive-in device of claim 2, wherein the fixing positions enclose a swiveling angle of substantially 90°.

4. (Original) The power-operated drive-in device of claim 3, wherein the drive-in device has a locking device (24) having at least one opening (26) at the head piece (4) in which a locking body (28) is held in a movable manner, the locking body (28) being pressed against the guide pipe (12) wherein at least two receptacles (34) with which the locking body (28) can engage.

5. (Original) The power-operated drive-in device of claim 4, wherein the locking body (28) is a ball.

6. (Original) The power-operated drive-in device of claim 4, wherein the locking body (28) is acted upon by pressure in a direction of the guide pipe (12) through a leaf spring (30).

7. (Original) The power-operated drive-in device of claim 3, wherein the drive-in device (2) has a locking device (24) with a locking screw (38) that can be positioned in one of at least two bore holes (40) at the guide pipe (12) by an end remote of the screw head through a screw receptacle (36) of the head piece (4).

8. (Original) The power-operated drive-in device of claim 7, wherein the drive-in device (2) has an axial securing device with a retaining pin (18) that is arranged in a receiving bore hole (16) of the head piece (4) transverse to the drive-in direction (14) when the head piece (4) is fixed to the rest of the drive-in device (2) and the retaining pin (18) projects partially into an annular groove